



# Peelable Solder Mask **IF 710**

INTERFLUX®  
ELECTRONICS N.V.



Technical data IF 710

Ver: 3.11 27-10-15

Page 1

## Natural latex based peelable solder mask

### Description:

The Interflux® **IF 710** Peelable Solder Mask is a natural latex based, temporary solder masking material.

It is typically being used in wave soldering applications where a part of the board needs to be protected from wave contact, e.g. for cases where a component is temporarily unavailable and needs to be soldered afterwards by hand or selective soldering.

**IF 710** has good adhesion, quick drying times and high tensile strength after processing for easy removal.

The cured product is compatible with virtually all fluxes and cleaning agents.

When using the product on bare Cu or Cu/OSP, it might give a discolouration of the Cu.

### Applying & curing

The product is squeezed out of the bottle onto the areas that need to be covered. It can also be applied by stencil printing or dispensing. The product's viscosity can be lowered by diluting it with DI water. This however might influence curing times. The uncured product can be removed with DI water. The thickness of the layer that is being ap-



Products pictured may differ from the product delivered

### Physical and chemical properties:

Specific density	: 1.091 g/ml ± 0.05
Appearance	: white viscous liquid
Odour	: slightly like ammonia
Solid content	: ± 60%
Viscosity	: 25 - 35 kcps
Dilution	: DI water

plied, has a large influence on the curing times. In general this is 0,5 mm to 1mm. General curing time at room temperature is about one hour. Curing times can be accelerated with temperature e.g. 15min @ 80°C. The product should not exceed 266°C in the process. It is not advisable to process the product without previous curing.



**RoHS**  
compliant

### More information:

Applying & Curing P.1

Storage and transport P.2

Packaging P.2

### Key advantages:

- Suitable for lead-free soldering up to 266°C
- Good adhesion
- Quick drying
- High tensile strength when cured
- Easy removal



## Storage and transport

**IF 710** has a shelf life of 6 months when stored in original containers at ambient temperatures (min. 5°C - max. 32°C).

Avoid temperatures below 5°C.

## Packaging:

**IF 710** is available in the following packaging:

250ml squeezable bottle

Trade name : IF 710 Peelable Soldermask

D i s c l a i m e r

Because Interflux® Electronics N.V. cannot anticipate or control the many different conditions under which this information and our products may be used, we do not guarantee the applicability or the accuracy of this information or the suitability of our products in any given situation. Users of our products should make their own test to determine the suitability of each such product for their particular purposes. The product discussed is sold without such warranty, either express or implied.

Copyright:

**INTERFLUX®** ELECTRONICS

Please consult the latest version of this document on:

[www.interflux.com](http://www.interflux.com)

This document in another language?:

[www.interflux.com](http://www.interflux.com)